





Exe Holding - EXIT 1H IP65



DATE ELECTRICE

Voltage [V]	230
Frecventa [Hz]	50
Putere [W]	3
Sursa	LED
Autonomie [h]	1
Tip	mentinut, test buton

DATE FOTOMETRICE

Flux luminos [lm]	300
Optica [°]	120
CRI [RA]	>80
CCT [K]	6400

DIMENSIUNI

Lungime [mm]	350
Latime [mm]	117
Inaltime [mm]	76

DATE TEHNICE

Montaj	APLICAT
Material	policarbonat
Finisaj	corp ALB
Protectie [IP]	65
Protectie impact [IK]	07
Temperatura [°C]	+5..+30
Durata medie [h]	40 000
Dimabil	NU



Bucharest, Romania Office: Aeroportului Str., No. 141th, Mogosoaia, Ilfov, Romania, PO Box 077135

Vienna, Austria Office: Martin Str., No 51st, Vienna, Austria, PO Box 1180

London, United Kingdom Office: 3rd The Shrubberies, George Lane, South Woodford, London, PO Box E18 1BG

New York, USA Office: 46-12 Queens Blvd. No. 205th, Sunnyside, NY., USA, PO Box 11104

WEB: www.exeholding.com **E-mail:** office@exeholding.com



STANDARD



ACCESORII SUPLIMENTARE

Pictograme



Grilaj protectie

