




EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

LINIAR LED EXE-P-A-IP40



DATE ELECTRICE


Voltage [V]	220-240
Frecventa [Hz]	50/60
Sursa	LED
Power factor PF	>0.9
CRI [RA]	>80
Optica	120°

DATE TEHNICE

Montaj	APLICAT
Material	ALUMINIU
Finisaj	ALB/NEGRU/RAL
Factor protectie [IP]	IP40
Factor protectie [IK]	IK08
Temperatura	5°C ... +30°C
Durata medie [h]	60000

MODELE

Cod	Descriere
EXE-P-A-14W-IP40	EXE LINIAR LED 14W, 1425LM, 2700/6500K, 104X347X48 mm, IP40
EXE-P-A-26W-IP40	EXE LINIAR LED 26W, 2850LM, 2700/6500K, 104X628X48 mm, IP40
EXE-P-A-39W-IP40	EXE LINIAR LED 39W, 4275LM, 2700/6500K, 104X908X48 mm, IP40
EXE-P-A-53W-IP40	EXE LINIAR LED 53W, 5700LM, 2700/6500K, 104X1189X48 mm, IP40



ISO 9001



ISO 14001



ISO 27001



ISO 45001



ISO 37001



ISO 50001

Romania Office & Production:

Aeroportului no.141 Street, Mogosoaia, Ilfov, PO 077135
www.exeholding.com; office@exeholding.com; Phone: +40 722 241 231