



# EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

## LINIAR LED EXE-P-GL-IP40



### DATE ELECTRICE


Voltage [V]	220-240
Frecventa [Hz]	50/60
Sursa	LED
Power factor PF	>0.9
CRI [RA]	>80
Optica	120°
Optional	dimabil/kit emergenta

### DATE TEHNICE

Montaj	SUSPENDAT
Material	ALUMINIU
Finisaj	ALB/NEGRU/RAL
Factor protectie [IP]	IP40
Factor protectie [IK]	IK08
Temperatura	5°C ... +30°C
Durata medie [h]	60000

### MODELE

Cod	Descriere
EXE-P-GL-14W-IP40	EXE LINIAR LED 14W, 1295LM, 2700/6500K, 90X598X73 mm, IP40
EXE-P-GL-21W-IP40	EXE LINIAR LED 21W, 1945LM, 2700/6500K, 90X598X73 mm, IP40
EXE-P-GL-21W-IP40	EXE LINIAR LED 21W, 1940LM, 2700/6500K, 90X879X73 mm, IP40
EXE-P-GL-30W-IP40	EXE LINIAR LED 30W, 2920LM, 2700/6500K, 90X879X73 mm, IP40
EXE-P-GL-26W-IP40	EXE LINIAR LED 26W, 2585LM, 2700/6500K, 90X1159X73 mm, IP40
EXE-P-GL-41W-IP40	EXE LINIAR LED 41W, 3890LM, 2700/6500K, 90X1159X73 mm, IP40
EXE-P-GL-33W-IP40	EXE LINIAR LED 33W, 3230LM, 2700/6500K, 90X1440X73 mm, IP40
EXE-P-GL-51W-IP40	EXE LINIAR LED 51W, 4865LM, 2700/6500K, 90X1440X73 mm, IP40



### Romania Office & Production:

Aeroportului no.141 Street, Mogosoaia, Ilfov, PO 077135  
[www.exeholding.com](http://www.exeholding.com); [office@exeholding.com](mailto:office@exeholding.com); Phone: +40 722 241 231