




EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

DOWNLIGHT LED EXE-GT-L2-IP54



DATE ELECTRICE

Voltage [V]	220-240
Frecventa [Hz]	50/60
Sursa	LED
Power factor PF	>0.5
CRI [RA]	>80
Optica	120°

DATE TEHNICE

Montaj	INCASTRAT
Material	PC
Finisaj	ALB
Factor protectie [IP]	IP54
Factor protectie [IK]	IK06
Temperatura	5°C ... +30°C
Durata medie [h]	25000

MODELE

Cod	Descriere
EXE-GT-L2-3W-IP54	EXE DOWNLIGHT LED 3W, 240LM, 4000K, ø90X24 mm, IP54
EXE-GT-L2-6W-IP54	EXE DOWNLIGHT LED 6W, 480LM, 4000K, ø90X24 mm, IP54
EXE-GT-L2-15W-IP54	EXE DOWNLIGHT LED 15W, 1200LM, 4000K, ø150X24 mm, IP54
EXE-GT-L2-24W-IP54	EXE DOWNLIGHT LED 24W, 1920LM, 4000K, ø225X24 mm, IP54



ISO 9001



ISO 14001



ISO 27001



ISO 45001



ISO 37001



ISO 50001

Romania Office & Production:

Aeroportului no.141 Street, Mogosoaia, Ilfov, PO 077135

www.exeholding.com; office@exeholding.com; Phone: +40 722 241 231