




# EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

## DOWNLIGHT LED EXE-GT-SA-IP40



### DATE ELECTRICE

Voltage [V]	175-250
Frecventa [Hz]	50/60
Sursa	LED
Power factor PF	>0.5
CRI [RA]	>80
Optica	120°

### DATE TEHNICE

Montaj	APLICAT/INCASTRAT
Material	PC
Finisaj	ALB
Factor protectie [IP]	IP40
Factor protectie [IK]	IK08
Temperatura	5°C ... +30°C
Durata medie [h]	40000

### MODELE

Cod	Descriere
EXE-GT-SA-7W-IP40	EXE DOWNLIGHT LED 7W, 675LM, 4000K, ø115X35 mm, IP40
EXE-GT-SA-14W-IP40	EXE DOWNLIGHT LED 14W, 1200LM, 4000K, ø177X35 mm, IP40
EXE-GT-SA-20W-IP40	EXE DOWNLIGHT LED 20W, 1600LM, 4000K, ø245X35 mm, IP40



### Romania Office & Production:

Aeroportului no.141 Street, Mogosoaia, Ilfov, PO 077135  
[www.exeholding.com](http://www.exeholding.com); [office@exeholding.com](mailto:office@exeholding.com); Phone: +40 722 241 231