




EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

DOWNLIGHT LED EXE-GT-SA2-IP40



DATE ELECTRICE

Voltage [V]	175-250
Frecventa [Hz]	50/60
Sursa	LED
Power factor PF	>0.5
CRI [RA]	>80
Optica	120°

DATE TEHNICE

Montaj	APLICAT/INCASTRAT
Material	PC
Finisaj	ALB
Factor protectie [IP]	IP40
Factor protectie [IK]	IK08
Temperatura	5°C ... +30°C
Durata medie [h]	40000

MODELE

Cod	Descriere
EXE-GT-SA2-9W-IP40	EXE DOWNLIGHT LED 9W, 675LM, 4000K, 115X35 mm, IP40
EXE-GT-SA2-16W-IP40	EXE DOWNLIGHT LED 16W, 1200LM, 4000K, 171X35 mm, IP40
EXE-GT-SA2-24W-IP40	EXE DOWNLIGHT LED 24W, 1800LM, 4000K, 226X35 mm, IP40



Romania Office & Production:

Aeroportului no.141 Street, Mogosoaia, Ilfov, PO 077135
www.exeholding.com; office@exeholding.com; Phone: +40 722 241 231