




EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

DOWNLIGHT LED EXE-GT-SO-IP54



DATE ELECTRICE

Voltage [V]	176-264
Frecventa [Hz]	50/60
Sursa	LED
Power factor PF	>0.5
CRI [RA]	>80
Optica	120°

DATE TEHNICE

Montaj	INCASTRAT
Material	PC
Finisaj	ALB
Factor protectie [IP]	IP54
Factor protectie [IK]	IK08
Temperatura	5°C ... +30°C
Durata medie [h]	25000

MODELE

Cod	Descriere
EXE-GT-SO-12W-IP54	EXE DOWNLIGHT LED 12W, 1200LM, 4000K, 120X120X20 mm, IP54
EXE-GT-SO-18W-IP54	EXE DOWNLIGHT LED 18W, 1800LM, 4000K, 170X170X20 mm, IP54
EXE-GT-SO-24W-IP54	EXE DOWNLIGHT LED 24W, 2400LM, 4000K, 225X225X20 mm, IP54



Romania Office & Production:

Aeroportului no.141 Street, Mogosoaia, Ilfov, PO 077135
www.exeholding.com; office@exeholding.com; Phone: +40 722 241 231