





EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

DOWNLIGHT LED EXE-P-BRD-IP40



DATE ELECTRICE

Voltage [V]	220-240
Frecventa [Hz]	50/60
Sursa	LED
Power factor PF	>0.9
CRI [RA]	>80
Optica	120°
Optional	dimabil/kit de emergenta

DATE TEHNICE

Montaj	INCASTRAT
Material	ALUMINIU
Finisaj	ALB
Factor protectie [IP]	IP40
Factor protectie [IK]	IK09
Temperatura	5°C ... +30°C
Durata medie [h]	60000

MODELE

Cod	Descriere
EXE-P-BRD-9W-IP40	EXE DOWNLIGHT LED 9W, 780LM, D: 108 mm, H: 55 mm, IP40
EXE-P-BRD-10W-IP40	EXE DOWNLIGHT LED 10W, 850LM, D: 130 mm, H: 50 mm, IP40
EXE-P-BRD-14W-IP40	EXE DOWNLIGHT LED 14W, 1200LM, D: 130 mm, H: 50 mm, IP40
EXE-P-BRD-11W-IP40	EXE DOWNLIGHT LED 11W, 950LM, D: 147 mm, H: 55 mm, IP40
EXE-P-BRD-15W-IP40	EXE DOWNLIGHT LED 15W, 1300LM, D: 150 mm, H: 55 mm, IP40
EXE-P-BRD-15W-IP40	EXE DOWNLIGHT LED 15W, 1320LM, D: 180 mm, H: 58 mm, IP40
EXE-P-BRD-19W-IP40	EXE DOWNLIGHT LED 19W, 1580LM, D: 200 mm, H: 55 mm, IP40
EXE-P-BRD-27W-IP40	EXE DOWNLIGHT LED 27W, 2020LM, D: 200 mm, H: 55 mm, IP40
EXE-P-BRD-19W-IP40	EXE DOWNLIGHT LED 19W, 1600LM, D: 240 mm, H: 58 mm, IP40
EXE-P-BRD-27W-IP40	EXE DOWNLIGHT LED 27W, 2040LM, D: 240 mm, H: 58 mm, IP40
EXE-P-BRD-30W-IP40	EXE DOWNLIGHT LED 30W, 2625LM, D: 240 mm, H: 58 mm, IP40



Romania Office & Production:

Aeroportului no.141 Street, Mogosoaia, Ilfov, PO 077135
www.exeholding.com; office@exeholding.com; Phone: +40 722 241 231