




# EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

## DOWNLIGHT LED EXE-P-SD-IP40



### DATE ELECTRICE


Voltage [V]	220-240
Frecventa [Hz]	50/60
Sursa	LED
Power factor PF	>0.9
CRI [RA]	>80
Optica	120°
Optional	dimabil/kit de emergenta

### DATE TEHNICE

Montaj	INCASTRAT
Material	ALUMINIU
Finisaj	ALB
Factor protectie [IP]	IP40
Factor protectie [IK]	IK09
Temperatura	5°C ... +30°C
Durata medie [h]	60000

### MODELE

Cod	Descriere
EXE-P-SD-10W-IP40	EXE DOWNLIGHT LED 10W, 505LM, 2700/6500K, D: 128 mm, H: 25 mm, IP40
EXE-P-SD-11W-IP40	EXE DOWNLIGHT LED 11W, 580LM, 2700/6500K, D: 150 mm, H: 25 mm, IP40
EXE-P-SD-15W-IP40	EXE DOWNLIGHT LED 15W, 765LM, 2700/6500K, D: 150 mm, H: 25 mm, IP40
EXE-P-SD-19W-IP40	EXE DOWNLIGHT LED 19W, 1035LM, 2700/6500K, D: 200 mm, H: 25 mm, IP40
EXE-P-SD-27W-IP40	EXE DOWNLIGHT LED 27W, 1380LM, 2700/6500K, D: 200 mm, H: 25 mm, IP40



### Romania Office & Production:

Aeroportului no.141 Street, Mogosoaia, Ilfov, PO 077135  
[www.exeholding.com](http://www.exeholding.com); [office@exeholding.com](mailto:office@exeholding.com); Phone: +40 722 241 231