



EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

LINIAR LED EXE-P-ES-IP40



DATE ELECTRICE


Voltage [V]	220-240
Frecventa [Hz]	50/60
Sursa	LED
Power factor PF	>0.9
CRI [RA]	>80
Optica	120°
Optional	dimabil/kit de emergenta

DATE TEHNICE

Montaj	APLICAT/SUSPENDAT
Material	ALUMINIU
Finisaj	ALB/NEGRU/RAL
Factor protectie [IP]	IP40
Factor protectie [IK]	IK08
Temperatura	5°C ... +30°C
Durata medie [h]	60000

MODELE

Cod	Descriere
EXE-P-ES-8W-IP40	EXE LINIAR LED 8W, 620LM, 2700/6500K, 165X418X37 mm, IP40
EXE-P-ES-14W-IP40	EXE LINIAR LED 14W, 1235LM, 2700/6500K, 165X699X37 mm, IP40
EXE-P-ES-21W-IP40	EXE LINIAR LED 21W, 1855LM, 2700/6500K, 165X980X37 mm, IP40
EXE-P-ES-26W-IP40	EXE LINIAR LED 26W, 2470LM, 2700/6500K, 165X1260X37 mm, IP40
EXE-P-ES-33W-IP40	EXE LINIAR LED 33W, 3090LM, 2700/6500K, 165X1540X37 mm, IP40



ISO 9001



ISO 14001



ISO 27001



ISO 45001



ISO 37001



ISO 50001

Romania Office & Production:

Aeroportului no.141 Street, Mogoșoaia, Ilfov, PO 077135

www.exeholding.com; office@exeholding.com; Phone: +40 722 241 231