



EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

LINIAR LED EXE-P-ESCM-IP40



DATE ELECTRICE


| | |
|-----------------|--------------------------|
| Voltage [V] | 220-240 |
| Frecventa [Hz] | 50/60 |
| Sursa | LED |
| Power factor PF | >0.9 |
| CRI [RA] | >80 |
| Optica | 120° |
| Optional | dimabil/kit de emergenta |

DATE TEHNICE

| | |
|-----------------------|---------------|
| Montaj | APLICAT |
| Material | ALUMINIU |
| Finisaj | ALB/NEGRU/RAL |
| Factor protectie [IP] | IP40 |
| Factor protectie [IK] | IK08 |
| Temperatura | 5°C ... +30°C |
| Durata medie [h] | 60000 |

MODELE

| Cod | Descriere |
|--------------------|--|
| EXE-P-ESM-53W-IP40 | EXE LINIAR LED 53W, 4940LM, 2700/6500K, 287X1201X37 mm, IP40 |
| EXE-P-ESM-53W-IP40 | EXE LINIAR LED 53W, 4940LM, 2700/6500K, 287X1170X37 mm, IP40 |
| EXE-P-ESM-66W-IP40 | EXE LINIAR LED 66W, 6175LM, 2700/6500K, 287X1502X37 mm, IP40 |
| EXE-P-ESM-66W-IP40 | EXE LINIAR LED 66W, 6175LM, 2700/6500K, 287X1479X37 mm, IP40 |



ISO 9001



ISO 14001



ISO 27001



ISO 45001



ISO 37001



ISO 50001

Romania Office & Production:

Aeroportului no.141 Street, Mogosoaia, Ilfov, PO 077135

www.exeholding.com; office@exeholding.com; Phone: +40 722 241 231