



EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

LINIAR LED EXE-P-ESMC-IP40



DATE ELECTRICE


Voltage [V]	220-240
Frecventa [Hz]	50/60
Sursa	LED
Power factor PF	>0.9
CRI [RA]	>80
Optica	120°
Optional	dimabil/kit emergenta

DATE TEHNICE

Montaj	APLICAT
Material	ALUMINIU
Finisaj	ALB/NEGRU/RAL
Factor protectie [IP]	IP40
Factor protectie [IK]	IK08
Temperatura	5°C ... +30°C
Durata medie [h]	60000

MODELE

Cod	Descriere
EXE-P-ESMC-26W-IP40	EXE LINIAR LED 26W, 2470LM, 2700/6500K, 165X1213X37 mm, IP40
EXE-P-ESMC-26W-IP40	EXE LINIAR LED 26W, 2470LM, 2700/6500K, 165X1170X37 mm, IP40
EXE-P-ESMC-33W-IP40	EXE LINIAR LED 33W, 3090LM, 2700/6500K, 165X1502X37 mm, IP40
EXE-P-ESMC-33W-IP40	EXE LINIAR LED 33W, 3090LM, 2700/6500K, 165X1479X37 mm, IP40



Romania Office & Production:

Aeroportului no.141 Street, Mogosoaia, Ilfov, PO 077135
www.exeholding.com; office@exeholding.com; Phone: +40 722 241 231