



EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

LINIAR LED EXE-P-ESMF-IP40



DATE ELECTRICE


Voltage [V]	220-240
Frecventa [Hz]	50/60
Sursa	LED
Power factor PF	>0.9
CRI [RA]	>80
Optica	120°
Optional	dimabil/kit de emergenta

DATE TEHNICE

Montaj	APLICAT
Material	ALUMINIU
Finisaj	ALB/NEGRU/RAL
Factor protectie [IP]	IP40
Factor protectie [IK]	IK08
Temperatura	5°C ... +30°C
Durata medie [h]	60000

MODELE

Cod	Descriere
EXE-P-ESMF-53W-IP40	EXE LINIAR LED 53W,4940LM, 2700/6500K, 486X692X37 mm, IP40
EXE-P-ESMF-79W-IP40	EXE LINIAR LED 79W,7410LM, 2700/6500K, 486X973X37 mm, IP40
EXE-P-ESMF-105W-IP40	EXE LINIAR LED 105W,9880LM, 2700/6500K, 486X1254X37 mm, IP40
EXE-P-ESMF-132W-IP40	EXE LINIAR LED 132W,12350LM, 2700/6500K, 486X1535X37 mm, IP40



Romania Office & Production:

Aeroportului no.141 Street, Mogosoaia, Ilfov, PO 077135
www.exeholding.com; office@exeholding.com; Phone: +40 722 241 231