



# EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

## LINIAR LED EXE-P-ESU-IP40



### DATE ELECTRICE


Voltage [V]	220-240
Frecventa [Hz]	50/60
Sursa	LED
Power factor PF	>0.9
CRI [RA]	>80
Optica	120°
Optional	dimabil/kit de emergenta

### DATE TEHNICE

Montaj	APLICAT/SUSPENDAT
Material	ALUMINIU
Finisaj	ALB/NEGRU/RAL
Factor protectie [IP]	IP40
Factor protectie [IK]	IK08
Temperatura	5°C ... +30°C
Durata medie [h]	60000

### MODELE

Cod	Descriere
EXE-P-ESU-14W-IP40	EXE LINIAR LED 14W, 1235LM, 2700/6500K, 287X418X37 mm, IP40
EXE-P-ESU-26W-IP40	EXE LINIAR LED 26W, 2470LM, 2700/6500K, 287X699X37 mm, IP40
EXE-P-ESU-39W-IP40	EXE LINIAR LED 39W, 3705LM, 2700/6500K, 287X1260X37 mm, IP40
EXE-P-ESU-53W-IP40	EXE LINIAR LED 53W, 4940LM, 2700/6500K, 287X1260X37 mm, IP40
EXE-P-ESU-66W-IP40	EXE LINIAR LED 66W, 6175LM, 2700/6500K, 287X1540X37 mm, IP40



ISO 9001



ISO 14001



ISO 27001



ISO 45001



ISO 37001



ISO 50001

### Romania Office & Production:

Aeroportului no.141 Street, Mogosoaia, Ilfov, PO 077135

[www.exeholding.com](http://www.exeholding.com); [office@exeholding.com](mailto:office@exeholding.com); Phone: +40 722 241 231