




EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

LINIAR LED EXE-P-FS-IP40



DATE ELECTRICE

Voltage [V]	220-240
Frecventa [Hz]	50/60
Sursa	LED
Power factor PF	>0.9
CRI [RA]	>80
Optica	120°
Optional	dimabil/kit de emergenta

DATE TEHNICE

Montaj	APLICAT/SUSPENDAT
Material	ALUMINIU
Finisaj	ALB/NEGRU/RAL
Factor protectie [IP]	IP40
Factor protectie [IK]	IK08
Temperatura	5°C ... +30°C
Durata medie [h]	60000

MODELE

Cod	Descriere
EXE-P-FS-14W-IP40	EXE LINIAR LED 14W, 1200LM, 2700/6500K, 57X570X85 mm, IP40
EXE-P-FS-21W-IP40	EXE LINIAR LED 21W, 1805LM, 2700/6500K, 57X570X85 mm, IP40
EXE-P-FS-21W-IP40	EXE LINIAR LED 21W, 1795LM, 2700/6500K, 57X850X85 mm, IP40
EXE-P-FS-30W-IP40	EXE LINIAR LED 30W, 2705LM, 2700/6500K, 57X850X85 mm, IP40
EXE-P-FS-26W-IP40	EXE LINIAR LED 26W, 2395LM, 2700/6500K, 57X1130X85 mm, IP40
EXE-P-FS-41W-IP40	EXE LINIAR LED 41W, 3605LM, 2700/6500K, 57X1130X85 mm, IP40
EXE-P-FS-33W-IP40	EXE LINIAR LED 33W, 2995LM, 2700/6500K, 57X1412X85 mm, IP40
EXE-P-FS-51W-IP40	EXE LINIAR LED 51W, 4505LM, 2700/6500K, 57X1412X85 mm, IP40
EXE-P-FS-39W-IP40	EXE LINIAR LED 39W, 3595LM, 2700/6500K, 57X1693X85 mm, IP40
EXE-P-FS-61W-IP40	EXE LINIAR LED 61W, 5405LM, 2700/6500K, 57X1693X85 mm, IP40
EXE-P-FS-47W-IP40	EXE LINIAR LED 47W, 4190LM, 2700/6500K, 57X1973X85 mm, IP40
EXE-P-FS-70W-IP40	EXE LINIAR LED 70W, 6310LM, 2700/6500K, 57X1973X85 mm, IP40
EXE-P-FS-53W-IP40	EXE LINIAR LED 53W, 4790LM, 2700/6500K, 57X2254X85 mm, IP40
EXE-P-FS-60W-IP40	EXE LINIAR LED 60W, 5390LM, 2700/6500K, 57X2534X85 mm, IP40



ISO 9001



ISO 14001



ISO 27001



ISO 45001



ISO 37001



ISO 50001

Romania Office & Production:


Aeroportului no.141 Street, Mogosoaia, Ilfov, PO 077135
www.exeholding.com; office@exeholding.com; Phone: +40 722 241 231



EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

EXE-P-FS-66W-IP40	EXE LINIAR LED 66W, 5985LM, 2700/6500K, 57X2815X85 mm, IP40
EXE-P-FS-33W-IP40	EXE LINIAR LED 33W, 2995LM, 2700/6500K, 57X1408X85 mm, IP40
EXE-P-FS-33W-IP40	EXE LINIAR LED 33W, 2995LM, 2700/6500K, 57X1404X85 mm, IP40
EXE-P-FS-51W-IP40	EXE LINIAR LED 51W, 4505LM, 2700/6500K, 57X1408X85 mm, IP40
EXE-P-FS-51W-IP40	EXE LINIAR LED 51W, 4505LM, 2700/6500K, 57X1404X85 mm, IP40
EXE-P-FS-39W-IP40	EXE LINIAR LED 39W, 3595LM, 2700/6500K, 57X1689X85 mm, IP40
EXE-P-FS-39W-IP40	EXE LINIAR LED 39W, 3595LM, 2700/6500K, 57X1695X85 mm, IP40
EXE-P-FS-61W-IP40	EXE LINIAR LED 61W, 5405LM, 2700/6500K, 57X1689X85 mm, IP40
EXE-P-FS-61W-IP40	EXE LINIAR LED 61W, 5405LM, 2700/6500K, 57X1685X85 mm, IP40
EXE-P-FS-47W-IP40	EXE LINIAR LED 47W, 4190LM, 2700/6500K, 57X1969X85 mm, IP40
EXE-P-FS-47W-IP40	EXE LINIAR LED 47W, 4190LM, 2700/6500K, 57X1965X85 mm, IP40
EXE-P-FS-70W-IP40	EXE LINIAR LED 70W, 6310LM, 2700/6500K, 57X1969X85 mm, IP40
EXE-P-FS-70W-IP40	EXE LINIAR LED 70W, 6310LM, 2700/6500K, 57X1965X85 mm, IP40
EXE-P-FS-53W-IP40	EXE LINIAR LED 53W, 4790LM, 2700/6500K, 57X2250X85 mm, IP40
EXE-P-FS-53W-IP40	EXE LINIAR LED 53W, 4790LM, 2700/6500K, 57X2246X85 mm, IP40
EXE-P-FS-60W-IP40	EXE LINIAR LED 60W, 5390LM, 2700/6500K, 57X22530X85 mm, IP40
EXE-P-FS-60W-IP40	EXE LINIAR LED 60W, 5390LM, 2700/6500K, 57X2526X85 mm, IP40
EXE-P-FS-66W-IP40	EXE LINIAR LED 66W, 5985LM, 2700/6500K, 57X2811X85 mm, IP40
EXE-P-FS-66W-IP40	EXE LINIAR LED 66W, 5985LM, 2700/6500K, 57X2807X85 mm, IP40



ISO 9001



ISO 14001



ISO 27001



ISO 45001



ISO 37001



ISO 50001

Romania Office & Production:

Aeroportului no.141 Street, Mogosoaia, Ilfov, PO 077135

www.exeholding.com; office@exeholding.com; Phone: +40 722 241 231