



EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

LINIAR LED EXE-P-OS-IP40



DATE ELECTRICE

Voltage [V]	220-240
Frecventa [Hz]	50/60
Sursa	LED
Power factor PF	>0.9
CRI [RA]	>80
Optica	120°
Optional	dimabil/kit emergenta

DATE TEHNICE

Montaj	APLICAT/SUSPENDAT/ INCASTRAT
Material	ALUMINIU
Finisaj	ALB/NEGRU/RAL
Factor protectie [IP]	IP40
Factor protectie [IK]	IK08
Temperatura	5°C ... +30°C
Durata medie [h]	60000



Romania Office & Production:

Aeroportului no.141 Street, Mogosoaia, Ilfov, PO 077135
www.exeholding.com; office@exeholding.com; Phone: +40 722 241 231





EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

MODEL

Cod	Descriere
EXE-P-OS-15W-IP40	EXE LINIAR LED 15W, 1375LM, 2700/6500K, 57X675X85 mm, IP40
EXE-P-OS-20W-IP40	EXE LINIAR LED 20W, 1815LM, 2700/6500K, 57X675X85 mm, IP40
EXE-P-OS-26W-IP40	EXE LINIAR LED 26W, 2210LM, 2700/6500K, 57X675X85 mm, IP40
EXE-P-OS-19W-IP40	EXE LINIAR LED 19W, 1830LM, 2700/6500K, 57X895X85 mm, IP40
EXE-P-OS-27W-IP40	EXE LINIAR LED 27W, 2420LM, 2700/6500K, 57X895X85 mm, IP40
EXE-P-OS-35W-IP40	EXE LINIAR LED 35W, 2945LM, 2700/6500K, 57X895X85 mm, IP40
EXE-P-OS-24W-IP40	EXE LINIAR LED 24W, 2285LM, 2700/6500K, 57X1115X85 mm, IP40
EXE-P-OS-33W-IP40	EXE LINIAR LED 33W, 3025LM, 2700/6500K, 57X1115X85 mm, IP40
EXE-P-OS-43W-IP40	EXE LINIAR LED 43W, 3680LM, 2700/6500K, 57X1115X85 mm, IP40
EXE-P-OS-29W-IP40	EXE LINIAR LED 29W, 2745LM, 2700/6500K, 57X1334X85 mm, IP40
EXE-P-OS-40W-IP40	EXE LINIAR LED 40W, 3630LM, 2700/6500K, 57X1334X85 mm, IP40
EXE-P-OS-51W-IP40	EXE LINIAR LED 51W, 4420LM, 2700/6500K, 57X1334X85 mm, IP40
EXE-P-OS-33W-IP40	EXE LINIAR LED 33W, 3200LM, 2700/6500K, 57X1554X85 mm, IP40
EXE-P-OS-47W-IP40	EXE LINIAR LED 47W, 4235LM, 2700/6500K, 57X1554X85 mm, IP40
EXE-P-OS-60W-IP40	EXE LINIAR LED 60W, 5155LM, 2700/6500K, 57X1554X85 mm, IP40
EXE-P-OS-38W-IP40	EXE LINIAR LED 38W, 3660LM, 2700/6500K, 57X1774X85 mm, IP40
EXE-P-OS-53W-IP40	EXE LINIAR LED 53W, 4840LM, 2700/6500K, 57X1774X85 mm, IP40
EXE-P-OS-69W-IP40	EXE LINIAR LED 69W, 5890LM, 2700/6500K, 57X1774X85 mm, IP40
EXE-P-OS-43W-IP40	EXE LINIAR LED 43W, 4115LM, 2700/6500K, 57X1994X85 mm, IP40
EXE-P-OS-60W-IP40	EXE LINIAR LED 60W, 5445LM, 2700/6500K, 57X1994X85 mm, IP40
EXE-P-OS-77W-IP40	EXE LINIAR LED 77W, 6625LM, 2700/6500K, 57X1994X85 mm, IP40
EXE-P-OS-48W-IP40	EXE LINIAR LED 48W, 4570LM, 2700/6500K, 57X2214X85 mm, IP40
EXE-P-OS-67W-IP40	EXE LINIAR LED 67W, 6050LM, 2700/6500K, 57X2214X85 mm, IP40
EXE-P-OS-86W-IP40	EXE LINIAR LED 86W, 7360LM, 2700/6500K, 57X2214X85 mm, IP40



ISO 9001



ISO 14001



ISO 27001



ISO 45001



ISO 37001



ISO 50001

Romania Office & Production:

Aeroportului no.141 Street, Mogosoaia, Ilfov, PO 077135

www.exeholding.com; office@exeholding.com; Phone: +40 722 241 231

ATENȚIE ! Acest document conține date cu caracter personal protejate de Regulamentul U.E. nr. 679/2016