




EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

LINIAR LED EXE-P-PS-IP40



DATE ELECTRICE

Voltage [V]	220-240
Frecventa [Hz]	50/60
Sursa	LED
Power factor PF	>0.9
CRI [RA]	>80
Optica	120°
Optional	dimabil/kit de emergenta

DATE TEHNICE

Montaj	INCASTRAT
Material	ALUMINIU
Finisaj	ALB/GRI
Factor protectie [IP]	IP40
Factor protectie [IK]	IK08
Temperatura	5°C ... +30°C
Durata medie [h]	60000



Romania Office & Production:

Aeroportului no.141 Street, Mogosoaia, Ilfov, PO 077135
www.exeholding.com; office@exeholding.com; Phone: +40 722 241 231




EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

MODEL

Cod	Descriere
EXE-P-PS-21W-IP40	EXE LINIAR LED 21W, 2140LM, 2700/6500K, 98X853X76 mm, IP40
EXE-P-PS-30W-IP40	EXE LINIAR LED 30W, 3220LM, 2700/6500K, 98X853X76 mm, IP40
EXE-P-PS-26W-IP40	EXE LINIAR LED 26W, 2850LM, 2700/6500K, 98X1133X76 mm, IP40
EXE-P-PS-41W-IP40	EXE LINIAR LED 41W, 4290LM, 2700/6500K, 98X1133X76 mm, IP40
EXE-P-PS-33W-IP40	EXE LINIAR LED 33W, 3565LM, 2700/6500K, 98X1414X76 mm, IP40
EXE-P-PS-33W-IP40	EXE LINIAR LED 33W, 3565LM, 2700/6500K, 98X1409X76 mm, IP40
EXE-P-PS-33W-IP40	EXE LINIAR LED 33W, 3565LM, 2700/6500K, 98X1404X76 mm, IP40
EXE-P-PS-51W-IP40	EXE LINIAR LED 51W, 5365LM, 2700/6500K, 98X1414X76 mm, IP40
EXE-P-PS-51W-IP40	EXE LINIAR LED 51W, 5365LM, 2700/6500K, 98X1409X76 mm, IP40
EXE-P-PS-51W-IP40	EXE LINIAR LED 51W, 5365LM, 2700/6500K, 98X1404X76 mm, IP40
EXE-P-PS-39W-IP40	EXE LINIAR LED 39W, 4275LM, 2700/6500K, 98X1695X76 mm, IP40
EXE-P-PS-39W-IP40	EXE LINIAR LED 39W, 4275LM, 2700/6500K, 98X1690X76 mm, IP40
EXE-P-PS-39W-IP40	EXE LINIAR LED 39W, 4275LM, 2700/6500K, 98X1685X76 mm, IP40
EXE-P-PS-61W-IP40	EXE LINIAR LED 61W, 6435LM, 2700/6500K, 98X1695X76 mm, IP40
EXE-P-PS-61W-IP40	EXE LINIAR LED 61W, 6435LM, 2700/6500K, 98X1690X76 mm, IP40
EXE-P-PS-61W-IP40	EXE LINIAR LED 61W, 6435LM, 2700/6500K, 98X1685X76 mm, IP40
EXE-P-PS-47W-IP40	EXE LINIAR LED 47W, 4990LM, 2700/6500K, 98X1971X76 mm, IP40
EXE-P-PS-47W-IP40	EXE LINIAR LED 47W, 4990LM, 2700/6500K, 98X1871X76 mm, IP40
EXE-P-PS-47W-IP40	EXE LINIAR LED 47W, 4990LM, 2700/6500K, 98X1966X76 mm, IP40
EXE-P-PS-70W-IP40	EXE LINIAR LED 70W, 7510LM, 2700/6500K, 98X1976X76 mm, IP40
EXE-P-PS-70W-IP40	EXE LINIAR LED 70W, 7510LM, 2700/6500K, 98X1971X76 mm, IP40
EXE-P-PS-70W-IP40	EXE LINIAR LED 70W, 7510LM, 2700/6500K, 98X1966X76 mm, IP40
EXE-P-PS-53W-IP40	EXE LINIAR LED 53W, 5700LM, 2700/6500K, 98X2256X76 mm, IP40
EXE-P-PS-53W-IP40	EXE LINIAR LED 53W, 5700LM, 2700/6500K, 98X2251X76 mm, IP40
EXE-P-PS-53W-IP40	EXE LINIAR LED 53W, 5700LM, 2700/6500K, 98X2246X76 mm, IP40
EXE-P-PS-60W-IP40	EXE LINIAR LED 60W, 6415LM, 2700/6500K, 98X2536X76 mm, IP40
EXE-P-PS-60W-IP40	EXE LINIAR LED 60W, 6415LM, 2700/6500K, 98X2531X76 mm, IP40
EXE-P-PS-60W-IP40	EXE LINIAR LED 60W, 6415LM, 2700/6500K, 98X2526X76 mm, IP40
EXE-P-PS-66W-IP40	EXE LINIAR LED 66W, 7125LM, 2700/6500K, 98X2816X76 mm, IP40
EXE-P-PS-66W-IP40	EXE LINIAR LED 66W, 7125LM, 2700/6500K, 98X2811X76 mm, IP40
EXE-P-PS-66W-IP40	EXE LINIAR LED 66W, 7125LM, 2700/6500K, 98X2806X76 mm, IP40



Romania Office & Production:

Aeroportului no.141 Street, Mogosoaia, Ilfov, PO 077135
www.exeholding.com; office@exeholding.com; Phone: +40 722 241 231