





EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

LINIAR LED EXE-P-VS-IP40



DATE ELECTRICE

Voltage [V]	220-240
Frecventa [Hz]	50/60
Sursa	LED
Power factor PF	>0.9
CRI [RA]	>80
Optica	120°
Optional	dimabil/kit emergenta

DATE TEHNICE

Montaj	APLICAT/SUSPENDAT
Material	ALUMINIU
Finisaj	ALB/NEGRU/RAL
Factor protectie [IP]	IP40
Factor protectie [IK]	IK08
Temperatura	5°C ... +30°C
Durata medie [h]	60000

MODELE

Cod	Descriere
EXE-P-VS-14W-IP40	EXE LINIAR LED 14W, 1295LM, 2700/6500K, 70X570X90 mm, IP40
EXE-P-VS-21W-IP40	EXE LINIAR LED 21W, 1945LM, 2700/6500K, 70X570X90 mm, IP40
EXE-P-VS-21W-IP40	EXE LINIAR LED 21W, 1940LM, 2700/6500K, 70X850X90 mm, IP40
EXE-P-VS-30W-IP40	EXE LINIAR LED 30W, 2920LM, 2700/6500K, 70X850X90 mm, IP40
EXE-P-VS-26W-IP40	EXE LINIAR LED 26W, 2585LM, 2700/6500K, 70X1130X90 mm, IP40
EXE-P-VS-41W-IP40	EXE LINIAR LED 41W, 3890LM, 2700/6500K, 70X1130X90 mm, IP40
EXE-P-VS-33W-IP40	EXE LINIAR LED 33W, 3230LM, 2700/6500K, 70X1412X90 mm, IP40
EXE-P-VS-51W-IP40	EXE LINIAR LED 51W, 4865LM, 2700/6500K, 70X1412X90 mm, IP40
EXE-P-VS-39W-IP40	EXE LINIAR LED 39W, 3880LM, 2700/6500K, 70X1693X90 mm, IP40
EXE-P-VS-61W-IP40	EXE LINIAR LED 61W, 5835LM, 2700/6500K, 70X1693X90 mm, IP40
EXE-P-VS-47W-IP40	EXE LINIAR LED 47W, 4525LM, 2700/6500K, 70X1973X90 mm, IP40
EXE-P-VS-70W-IP40	EXE LINIAR LED 70W, 6810LM, 2700/6500K, 70X1973X90 mm, IP40
EXE-P-VS-53W-IP40	EXE LINIAR LED 53W, 5170LM, 2700/6500K, 70X2254X90 mm, IP40
EXE-P-VS-60W-IP40	EXE LINIAR LED 60W, 5185LM, 2700/6500K, 70X2534X90 mm, IP40
EXE-P-VS-66W-IP40	EXE LINIAR LED 66W, 6460LM, 2700/6500K, 70X2815X90 mm, IP40



Romania Office & Production:


Aeroportului no.141 Street, Mogosoaia, Ilfov, PO 077135
www.exeholding.com; office@exeholding.com; Phone: +40 722 241 231



EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

EXE-P-VS-33W-IP40	EXE LINIAR LED 33W, 3230LM, 2700/6500K, 70X1408X90 mm, IP40
EXE-P-VS-33W-IP40	EXE LINIAR LED 33W, 3230LM, 2700/6500K, 70X1404X90 mm, IP40
EXE-P-VS-51W-IP40	EXE LINIAR LED 51W, 4865LM, 2700/6500K, 70X1408X90 mm, IP40
EXE-P-VS-51W-IP40	EXE LINIAR LED 51W, 4865LM, 2700/6500K, 70X1404X90 mm, IP40
EXE-P-VS-39W-IP40	EXE LINIAR LED 39W, 3880LM, 2700/6500K, 70X1689X90 mm, IP40
EXE-P-VS-39W-IP40	EXE LINIAR LED 39W, 3880LM, 2700/6500K, 70X1685X90 mm, IP40
EXE-P-VS-61W-IP40	EXE LINIAR LED 61W, 5835LM, 2700/6500K, 70X1689X90 mm, IP40
EXE-P-VS-61W-IP40	EXE LINIAR LED 61W, 5835LM, 2700/6500K, 70X1685X90 mm, IP40
EXE-P-VS-47W-IP40	EXE LINIAR LED 47W, 4525LM, 2700/6500K, 70X1969X90 mm, IP40
EXE-P-VS-47W-IP40	EXE LINIAR LED 47W, 4525LM, 2700/6500K, 70X1965X90 mm, IP40
EXE-P-VS-70W-IP40	EXE LINIAR LED 70W, 6810LM, 2700/6500K, 70X1969X90 mm, IP40
EXE-P-VS-70W-IP40	EXE LINIAR LED 70W, 6810LM, 2700/6500K, 70X1965X90 mm, IP40
EXE-P-VS-53W-IP40	EXE LINIAR LED 53W, 5170LM, 2700/6500K, 70X2250X90 mm, IP40
EXE-P-VS-53W-IP40	EXE LINIAR LE, 53W, 5170LM, 2700/6500K, 70X2246X90 mm, IP40
EXE-P-VS-60W-IP40	EXE LINIAR LED 60W, 5815LM, 2700/6500K, 70X2530X90 mm, IP40
EXE-P-VS-66W-IP40	EXE LINIAR LED 66W, 6460LM, 2700/6500K, 70X2811X90 mm, IP40
EXE-P-VS-66W-IP40	EXE LINIAR LED 66W, 6460LM, 2700/6500K, 70X2807X90 mm, IP40



Romania Office & Production:

Aeroportului no.141 Street, Mogosoaia, Ilfov, PO 077135
www.exeholding.com; office@exeholding.com; Phone: +40 722 241 231