




EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

PANEL LED EXE-GT-K-IP54



DATE ELECTRICE

Voltage [V]	220-240
Frecventa [Hz]	50/60
Sursa	LED
Power factor PF	>0.9
CRI [RA]	>80
Optica	120°
Optional	dimabil

DATE TEHNICE

Montaj	INCASTRAT
Material	ALUMINIU
Finisaj	ALB
Factor protectie [IP]	IP54
Factor protectie [IK]	IK08
Temperatura	5°C ... +30°C
Durata medie [h]	40000

MODELE

Cod	Descriere
EXE-GT-K1-24W-IP54	EXE PANEL LED 24W, 1800LM, 4000K, 595X295X10 mm, IP54
EXE-GT-K2-24W-IP54	EXE PANEL LED 24W, 1800LM, 3000K, 595X295X10 mm, IP54
EXE-GT-K3-42W-IP54	EXE PANEL LED 42W, 3200LM, 4000K, 595X595X10 mm, IP54
EXE-GT-K4-42W-IP54	EXE PANEL LED 42W, 3200LM, 3000K, 595X595X10 mm, IP54
EXE-GT-K5-42W-IP54	EXE PANEL LED 42W, 3200LM, 4000K, 1195X295X10 mm, IP54
EXE-GT-K6-42W-IP54	EXE PANEL LED 42W, 1800LM, 3000K, 1195X295X10 mm, IP54



Romania Office & Production:

Aeroportului no.141 Street, Mogosoaia, Ilfov, PO 077135
www.exeholding.com; office@exeholding.com; Phone: +40 722 241 231



EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

ACCESORII



KIT DE SUSPENSIE 1,5m



RAMA MONTAJ APARENT:

- 625X625X43 mm
- 600X600X43 mm
- 1200X300X43 mm
- 600X600X43 mm
- 1200X300X43 mm



SET MONTAJ PANOU INCASTRAT



SET MONTAJ TAVAN ZIDARIE



Romania Office & Production:

Aeroportului no.141 Street, Mogosoaia, Ilfov, PO 077135
www.exeholding.com; office@exeholding.com; Phone: +40 722 241 231