




# EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

## SPOT LED EXE-GT-A



### DATE ELECTRICE

Voltage [V]	220-240
Frecventa [Hz]	50/60
Sursa	LED
Power factor PF	>0.9
CRI [RA]	>80
Optica	110°

### DATE TEHNICE

Montaj	INCASTRAT
Material	ALUMINIU
Finisaj	ALB
Factor protectie [IP]	IP20/54
Factor protectie [IK]	IK08
Temperatura	5°C ... +35°C
Durata medie [h]	40000

### MODELE

Cod	Descriere
EXE-GT-A-18W-IP20/54	EXE SPOT LED 18W, 1800LM, 3000/4000/6400K, ø145X30 mm, IP20/54
EXE-GT-A-25W-IP20/54	EXE SPOT LED 25W, 2500LM, 3000/4000/6400K, ø190X30 mm, IP20/54
EXE-GT-A-35W-IP20/54	EXE SPOT LED 35W, 3500LM, 3000/4000/6400K, ø225X30 mm, IP20/54



#### Romania Office & Production:

Aeroportului no.141 Street, Mogosoaia, Ilfov, PO 077135  
[www.exeholding.com](http://www.exeholding.com); [office@exeholding.com](mailto:office@exeholding.com); Phone: +40 722 241 231