




EXE GREEN HOLDING

ENERGY EFFICIENCY SOLUTIONS

SPOT LED EXE-GT-S



DATE ELECTRICE

| | |
|-----------------|---------|
| Voltage [V] | 220-240 |
| Frecventa [Hz] | 50/60 |
| Sursa | LED |
| Power factor PF | >0.5 |
| CRI [RA] | >80 |
| Optica | 120° |

DATE TEHNICE

| | |
|-----------------------|---------------|
| Montaj | INCASTRAT |
| Material | ALUMINIU |
| Finisaj | ALB |
| Factor protectie [IP] | IP20/54 |
| Factor protectie [IK] | IK07 |
| Temperatura | 5°C ... +30°C |
| Durata medie [h] | 40000 |

MODELE

| Cod | Descriere |
|----------------------|--|
| EXE-GT-S-6W-IP20/54 | EXE SPOT LED 6W, 420LM, 4000K, ø100X90X60 mm, IP20/54 |
| EXE-GT-S-12W-IP20/54 | EXE SPOT LED 12W, 880LM, 4000K, ø130X110X65 mm, IP20/54 |
| EXE-GT-S-18W-IP20/54 | EXE SPOT LED 18W, 1350LM, 4000K, ø160X150X75 mm, IP20/54 |
| EXE-GT-S-24W-IP20/54 | EXE SPOT LED 24W, 1600LM, 4000K, ø190X175X75 mm, IP20/54 |



ISO 9001



ISO 14001



ISO 27001



ISO 45001



ISO 37001



ISO 50001

Romania Office & Production:

Aeroportului no.141 Street, Mogosoaia, Ilfov, PO 077135
www.exeholding.com; office@exeholding.com; Phone: +40 722 241 231